Loewe Life - Concept L 32 DVB-T/C Pure TV pleasure.

- High-definition LCD TV (HD ready) with brilliant picture in 16:9 format and 80 cm screen diagonal.
- Integrated DVB-T/-C. Digital satellite reception and common interface as retrofit.
- Convenient user guide thanks to Assist+. Excellent audio experience thanks to the CRX® sound system.

Technical information

Image:

- Automatic Movie Detection (AMD)
- Brightness cd/m²: 450
- Chassis: Digital+ (L2650) Colour Transient Improvement (CTI)
- Contrast: 800 : 1
- Diagonal Contour Control (DCC)
- Digital Comb Filter Plus
- Digital Line Control (DLC)
- Digital Line Interpolation (DLI) Digital Motion Interpolation Plus (DMI Plus)
- Digital Noise Control (DNC)
- Digital Scene Control (DSC)
- Digital Transient Improvement Plus (DTI Plus)
- Downscaling/upscaling
- Format options: 16 : 9, 4 : 3, Panorama, Cine, Zoom
- Fully digitised signal processing: 9 bit
- HD LCD Technology HD ready
- Horizontal and vertical viewing angle: 170°
- Image resolution: 1.366 x 768
- Luminance Transition Improvement (LTI)
- Picture format: 16 : 9
- PIP (AV)
- Screen diagonal in cm: 80
- Split Screen TV/Teletext Vertical image correction

Audio:

- Audio power amplifier output in watts (at 4 Ohms): 2 x 20
- DIS-Modul (Digital Input Selector)
- Fullrange speakers
- Number of speakers: 4
- Panorama
- Sound+ with CRX® sound system Virtual Dolby Surround [1]

Radio:

- Automatic station identification
- Programme positions: 1.670
- Radio function: with DVB-C, DVB-S

Operation:

Assist+

Article number EAN

65442D89

65442Y89

Automatic Channel Programming (ACP)

401188086028

401188084109

- Automatic shut-off
- Automatic Signal Switch (ASS)
- Automatic Volume Control (AVC) [2]
- Content-sensitive help
- Current TV Programme
- Digital Link
- Digital Link Plus
- Electronic Instruction Manual
- н. Electronic Program Guide (EPG) [3]
- . Index
- L-Link NexTView-Link [3]
- On Screen Display (OSD) in foreign languages: D-E-I-F-NL-GB-P-PL-CZ-DK-S-HU-FIN-SLN-TR-SK-RS-GR Parental Lock Plus
- Personalised teletext with direct access to bookmarked pages
- Power switch
- Programme positions (incl. AV): 1.670
- Remote control: RC 5
- Standard values can be stored individually
- Teletext: TOP-/FLOF Teletext/Level 2.5
- Teletext page memory: 1.500
- Video Timer

Reception

- Audio standard: BG/DK, Nicam, BG/L, I, DK
- Colour standard: PAL, Secam, NTSC, NTSC 4,43 MHz Hybrid tuner DVB-T, DVB-C, terrestrial analogue, cable
- analogue [4] Hyper-band (8-MHz) including special channels
- Television standard: PAL: B/G, D/K, I, L, M/M; PAL 60; Secam: B/G, D/K, L, NTSC, NTSCV

Connectors:

Colour options

Anthracite

Chrome Silver

- Antenna (analogue/digital)
- Audio In (Cinch)
- Audio Out Stereo (Cinch): controlled
- Component input YUV
- Copy function Euro-AV <-> Euro-AV
- Copy function Front-AV --> Euro-AV

97.0

Tabletop solution

Total depth: 23,2

TV depth: 10,0

- Digital-Audio Out (Cinch): 1
- Euro-AV/Scart total: 2
- Euro-AV/Scart, of which the following number are Component Video Input-ready: 1
- Euro-AV/Scart, of which the following number are RGB-ready: 1

97,0

Wall solution

OEWE.

TV depth: 10,0

Total depth: 11.2

51.2

- Euro-AV/Scart, of which the following number are S-VHS/Hi8-ready: 2
- Front-AV: on side of device
- HDMI including HDCP Headphones: 3.5 mm
- Hosiden input
- VGA

Optional function upgrades:

- Common interface
- DVB-S (Single-Tuner) [5]
- PIP (analogue)

Accessories

[2]

[4]

[5]

- Standard feature: Table base
- Wall Mount: WM 54
- Miscellaneous:
- Annual power in kWh: 141
- Mains voltage: 220-240 V, 50/60 Hz
- Nominal power in watts: 85
- Power consumption in standby mode in watts: 2.4 Power consumption in watts when the set is turned off: 0

Weight (approx.) on table base in kg: 18.5

Weight (approx.) in kg, not including table base: 16.5

[1] Dolby is a registered trademark of the Dolby Laboratories Licensing Corporation.

A number of Loewe televisions are also available as fully interactive Freeview compliant sets. Not available for special UK variants.

Function depends on signal format emitted by station

Works only with channels broadcasting NexTView data

VDE-safety standard (inspection seal)